### LEDme® PRO AC-LED LIGHT BARS

# WAC LIGHTING

### Responsible Lighting®



## **PRODUCT DESCRIPTION**

**BA-ACLED** 

Bringing out the best in bold, eye-catching residential, retail and commercial displays, LEDme® PRO AC-LED Light Bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crafted for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.

#### **FEATURES**

- High CRI 90+
- Does not require any driver or transformer
- · True 1" profile
- Backlighting with parabolic reflector allows a high uniformity of light
- No hotspots on countertop
- · Each light bar includes one "I" connector
- Minimal space between diffusers for a visually seamless line of illumination
- Free of projected heat, UV and IR radiation
- 90,000 hour rated life
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

Extruded aluminum body with polycarbonate lens. **Construction:** 

**Power:** Direct 120VAC 60Hz input.

2700K or 3000K AC LEDs. CRI: 90. **Light Source:** 

**Dimming:** May be dimmed down to 10% with electronic low voltage

(ELV) dimmer. Compatible with LUTRON DVELV-300, SELV-300

Electronic Low Voltage dimmer

Abrasion resistant Bronze (BZ), Brushed Aluminum (AL) and Finish:

White (WT) powder coat.

Standards: Title 24 CEC Compliant. Energy Star Rated. ETL & cETL Listed.

Fixture Type:
Catalog Number:
Project:
Location:

#### **FIXTURE PERFORMANCE**

Model #	Color Temp	Power	Lumens	Efficacy	
BA-ACLED8-927	2700K	5.5W	250	45 Lm/W	
BA-ACLED8-930	3000K 5.5W		255	46 Lm/W	
BA-ACLED12-927	2700K	8W	360	45 Lm/W	
BA-ACLED12-930	3000K	8W	365	46 Lm/W	
BA-ACLED18-927	2700K	10W	445	45 Lm/W	
BA-ACLED18-930	3000K	10W	450	45 Lm/W	
BA-ACLED24-927	2700K	15W	700	47 Lm/W	
BA-ACLED24-930	3000K	15W	705	47 Lm/W	
BA-ACLED30-927*	2700K	17W	765	45 Lm/W	
BA-ACLED30-930*	3000K	17W	785	46 Lm/W	

<sup>\*</sup> Not Title 24 compliant

#### **ACCESSORIES**

6' power cord			
	BA-PC6-WT		Supplies power in any application.
"I" connector			Interconnection for
	BA-I-WT		seamless end to end
			transitions. One included with each light bar.
Interconnect cable			
	BA-IC12-WT	12"	Links two light bars
	BA-IC24-WT	24"	using a single power
	BA-IC36-WT	36"	connection.

#### **ORDER NUMBER**

Model#	Leng	jth	Colo	Temp	Finis	h
BA-ACLED	8 12 18 24 30	8" 12" 18" 24" 30"	927 930	2700K 3000K	BZ AL WT	Bronze Brushed Aluminum White



Example: BA-ACLED12-927-AL

# **FINISHES**







**WAC Lighting** www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

**Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585