DOUBLE SPOT

Endurance Wallpack

WAC LIGHTING

Responsible Lighting®



_	-	\sim			-				DT	
μ	к	()	1)	u		1)1	. > (кі	\mathbf{P}	ION

Die cast aluminum factory sealed housings with patent pending design for a water and dust proof IP66 rated outdoor luminaire

FEATURES

- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Energy Star® rated
- Die-Cast Aluminum Construction
- 120V Direct Wire No Driver Needed
- Photo/Motion Sensor Sold Separately
- Smooth and Continuous ELV Dimming

Fixture Type:
Catalog Number:
Project:
Location:

SPECIFICATIONS

Construction: Die-cast aluminum **Power:** Line Voltage input (120V)

CRI: 85

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Bronze, and White

Standards: Energy Star®, IP66, Wet Location, ETL & cETL Listed **Operating Temperature:** -40°C (-40°F) to 40°C (104°F)

Rated Life: 43,000 hours

ORDER NUMBER

	Power	Comparable	Color	Temp	Delivered Lumens	Finish		
WP-LED430	30W	150W Halogen	30 50	3000K 5000K	965 x2 1030 x 2	aBZ aWT	Architectural Bronze Architectural White	
						'		

Example: WP-LED430-30-aWT

ACCESSORIES



Photocell Sensor PC-120-BK Black PC-120-GY Gray PC-120-WT White

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585