### R4RAL, R4SAL

### 4.5" Volta - Adjustable Invisible Trim

# WAC LIGHTING

### Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for the architectural lighting industry. This high lumen family of fixtures, with an extensive set of round and square fittings enables lighting designers an advanced system for a clean, uncluttered ceiling

#### **FEATURES**

- Dual finishes are single piece, no physical seams
- Center beam alignment retained throughout adjustment range
- 0-45° vertical and 365° horizontal lockable hot aiming
- Compatible with wide range of accessories

#### **SPECIFICATIONS**

**Construction:** Durable die-cast self flanged aluminum construction

**Input:** 120 - 277VAC

**Dimming:** Electronic Low Voltage (ELV): 100%-5%

0-10V: 100%-0%

**Mounting:** Two heavy gauge retention clips hold trim firmly

Accomodates 1/2 "- 1 1/2" ceiling thickness

**Finish:** Powder coated white, black and haze

Standards: ETL & cETL Wet location Listed

#### TRIMS (ORDER HOUSING SEPARATELY)

			Reference	e Output*					
Model		Beam Angle	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim	
67/8"	R4RAL Round	S 15° N 25° F 45°	1251 2366 2201	11865 7173 3947	827 2700K 927 2700K 830 3000K 930 3000K 835 3500K 840 4000K	85 90 85 90 85 85	BK HZ WT	Black Haze White	
max —4½"—	<b>R4SAL</b> Square	S 15° N 25° F 45°	1208 1653 1342	12465 8308 2313	827 2700K 927 2700K 830 3000K 930 3000K 835 3500K 840 4000K	85 90 85 90 85 85	BK HZ WT	Black Haze White	

<sup>\*</sup>Reference output shows 830(80CRI 3000K) trim with 36 housing. Use multiplier table below to determine the output for other combinations.

Multin	lior			TR	IM		
Multip	iler	827	927	830	930	835	840
	36	0.937	0.764	1.000	0.815	1.045	1.054
HOUSING	25	0.685	0.558	0.731	0.596	0.764	0.770
	15	0.456	0.371	0.486	0.396	0.508	0.512

R4\_\_AL-\_\_\_-

Example: R4RAL-S827-WT

Please see next page for housing units(required)

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

### **R4RAL, R4SAL**

# WAC LIGHTING

### 4.5" Volta - Adjustable Invisible Trim

### Responsible Lighting®

#### **HOUSINGS (REQUIRED)**

		Model		Power*	S	N, F	Rating	Opti	ons
New Contruction, Airtight  65%"  36"  1711/16"  223/16"	13½" (EM option)	R4RNL R4RCL	Round Round Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM	Emergency backup battery (Optional)
New Contruction, Airtight  65%"  36"  1711/16"  223/16"	13½" (EM option)	R4SNL R4SCL	Square Square Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM	Emergency backup battery (Optional)

<sup>\*</sup>Power consumption depends on beam angle of the trim.

R4\_\_\_\_-

Example: R4RNL-15 or R4RNL-15EM (with Emergency backup battery)



Accessory noider	
LENS-73-HLD	Required to hold lens and glare control accessories
Glare control access	sories
LENS-73-HCL LENS-73-CRL	Honeycomb Louver Cross Louver

Snoot

ENS-73-AMB	Amber lens
LENS-73-RED	Red lens
LENS-73-FR	Frosted lens
LENS-73-SPR	Spread lens
LENS-73-BEL	Beam Elongating

REF-R4-N	Narrow beam reflector
REF-R4-F	Flood beam reflector
REF-R4-W	Wide beam reflector

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

LENS-73-SNOOT

**Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760


## R4RAL, R4SAL

WAC LIGHTING

4.5" Volta - Adjustable Invisible Trim

Responsible Lighting®

#### FIELD CHANGEABLE AIMING



0 - 45° vertical lockable hot aiming



365° horizontal lockable hot aiming