


EXTERMINATOR II - model: MO-1014

Monopoint Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Museum-quality LED luminaire with high performance optics

FEATURES

- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum with removable front cap for easy change of lenses or accessories

Power Consumption: 14W

Input: 120V AC 50/60HZ

Dimming: Electronic low voltage (ELV) dimmer 100%-5% (120V only)

Finish: Powder coated

Standards: UL & cUL listed

ORDER NUMBER

Model	Beam	Color Temp	CRI	Lumens	CBCP	Finish
MO-1014	N 20°	827 2700K	85	860	4752	BK Black WT White
		927 2700K	90	627	3520	
		830 3000K	85	872	4826	
		930 3000K	90	677	3640	
		835 3500K	85	912	4597	
		840 4000K	85	965	4585	
	F 40°	827 2700K	85	852	1844	BK Black WT White
		927 2700K	90	624	1357	
		830 3000K	85	857	1955	
		930 3000K	90	663	1468	
		835 3500K	85	917	2001	
		840 4000K	85	980	2117	

MO-1014 - -

Example: MO-1014N-927-WT

Accommodates one lens accessory and one glare control accessory

LENS ACCESSORIES

Amber	LENS-11-AMB
Blue	LENS-11-BLU
Green	LENS-11-GRN
Red	LENS-11-RED
Yellow	LENS-11-YEL
Frosted	LENS-11-FR
Spread	LENS-11-SPR
Beam Elongating	LENS-11-BEL

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-11P-CRL-BK LENS-11P-CRL-WT
Snoot	LENS-11-SNOOT-BK LENS-11-SNOOT-WT

REFLECTORS

20°	SL-REF-CXA1310-N
40°	SL-REF-CXA1310-F

EXTENSIONS Sold as a complete unit

X6 6"	MO1014	N F	827	BK WT
X12 12"			927	
X18 18"			830	
X24 24"			930	
X36 36"			835	
			840	

Example: X12-MO1014N930WT

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585