
TUBE ARCHITECTURAL DS-WS05(CC) WAC LIGHTING

Color Changing LED Wall Mounts

Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- · High performance LED wall mount light
- Can be mounted upwards or downwards
- Solid die cast aluminum construction
- 5 year warranty
- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight™ iOS App.

SPECIFICATIONS

Universal voltage 120V - 277VAC, 50/60Hz Input:

Controls: DMX512, Bluetooth v4.0. Configured with ilumenight™ iOS App **Dimming:** 100%-1% in CCT & Color via DMX or Bluetooth control.

Light Source: High Output 2 Step Mac Ellipse Module, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated, white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

	Diameter	neter Power Beam		Delivered Lumens at 3000K	CBCP at 3000K Light Direction		Color Temp	Finish			
Single	DS-WS05 5"	31W	S 15° N 25° F 33°	835 785 775	6368 2170 1504	S Straight up or down					
			F	960	-	A Away from the wall	cc Color Changing	BK Black WT White BZ Bronze GH Graphite			
			F			B Towards the wall					

DS-WS05-Example: DS-WS05-FA-CC-BK






TUBE ARCHITECTURAL DS-WD05(CC) WAC LIGHTING

Color Changing LED Wall Mounts

Responsible Lighting®





-	
Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- · High performance LED wall mount light
- · Up and down light
- · Solid die cast aluminum construction
- 5 year warranty
- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight[™] iOS App.

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz

Controls: DMX512, Bluetooth v4.0. Configured with ilumenight™ iOS App **Dimming:** 100%-1% in CCT & Color via DMX or Bluetooth control.

Light Source: High Output 2 Step Mac Ellipse Module, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated, white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

	Diameter	Power	Веа	ım	Delivered Lumens at 3000K	CBCP at 3000K	Lig	Light Direction		Colc	or Temp	Finish		
Double	DS-WD05 5"	31W x2	S N F	15° 25° 33°	835 x2 785 x2 775 x2	6368 x2 2170 x2 1504 x2	s	Straight up or down		- CC Color Changing				
			F		960 x2	-	A	Away from the wall			BK WT	Black White		
				F			В	Towards the wall				Bronze Graphite		
							c	One side each						

DS-WD05-___-CC-__ Example: DS-WD05-FA-CC-BK



