

# Oberon

## Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	<b>Delivered Lumens</b>	Title 24
WS-W45714 14"	<b>3000K</b> 90	<b>BK</b> Black	19.4W	1865	685	Yes

Example: WS-W45714-BK

•For 277V special order, add an "F" before the finish: WS-W45714F-BK

For custom requests please contact customs@waclighting.com

#### **DESCRIPTION**

A timeless contemporary guardian. Oberon features a bent opal glass that provides even illumination with a solid Die-cast aluminum frame that is weather resistant and powder coated. The light engine is factory sealed for maximum protection against the harshest elements.

## **FEATURES**

- Bent opal glass provides even illumination
- Weather resistant powder coated finish
- Modern elegance brought to your backyard
- Light engine is factory sealed for maximum protection from the elements
- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

## **SPECIFICATIONS**

3000K Color Temp:

120 VAC,50/60Hz Input:

90 CRI:

ELV: 100-10% Dimming: 54000 Hours Rated Life:

Mounting: Can be mounted on wall in all orientations

ETL, cETL,IP65,Title 24 JA8-2019 Compliant,Dark Sky Standards:

Friendly

Wet Location Listed

Aluminum hardware with glass diffuser Construction:






Black

**LINE DRAWING:** 

#### REPLACEMENT PARTS

RPL-GLA-45714 - Glass for WS-W45714



WS-W45714





# Oberon

# Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	<b>LED Lumens</b>	<b>Delivered Lumens</b>	Title 24
WS-W45720 20"	<b>3000K</b> 90	BK Black	19.5W	1900	745	Yes

Example: WS-W45720-BK

•For 277V special order, add an "F" before the finish: WS-W45720F-BK

For custom requests please contact customs@waclighting.com

#### **DESCRIPTION**

A timeless contemporary guardian. Oberon features a bent opal glass that provides even illumination with a solid Die-cast aluminum frame that is weather resistant and powder coated. The light engine is factory sealed for maximum protection against the harshest elements.

## **FEATURES**

- Bent opal glass provides even illumination
- Weather resistant powder coated finish
- Modern elegance brought to your backyard
- Light engine is factory sealed for maximum protection from the elements
- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

## **SPECIFICATIONS**

Color Temp: 3000K

Input: 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant,Dark Sky

Friendly

Wet Location Listed

Construction: Aluminum hardware with glass diffuser



RPL-GLA-45720 - Glass for WS-W45720




#### **FINISHES:**



Black

**LINE DRAWING:** 



WS-W45720



# Oberon

# Outdoor Wall Sconce 3000K

Catalog Number:
Project:
Location:

Fixture Type:

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	<b>Delivered Lumens</b>	Title 24
WS-W45726 26"	<b>3000K</b> 90	<b>BK</b> Black	35W	3273	1027	Yes

Example: WS-W45726-BK

•For 277V special order, add an "F" before the finish: WS-W45726F-BK

For custom requests please contact customs@waclighting.com

#### **DESCRIPTION**

A timeless contemporary guardian. Oberon features a bent opal glass that provides even illumination with a solid Die-cast aluminum frame that is weather resistant and powder coated. The light engine is factory sealed for maximum protection against the harshest elements.

## **FEATURES**

- Bent opal glass provides even illumination
- Weather resistant powder coated finish
- Modern elegance brought to your backyard
- Light engine is factory sealed for maximum protection from the elements
- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

## **SPECIFICATIONS**

Color Temp: 3000K

Input: 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

**Construction:** Aluminum hardware with glass diffuser

#### REPLACEMENT PARTS

RPL-GLA-45726 - Glass for WS-W45726




## **FINISHES:**



Black

#### **LINE DRAWING:**



WS-W45726