



CATALOG NUMBER	TYPE
PROJECT	

LOW VOLTAGE ELECTRONIC TRANSFORMER

MODEL EN-1260-P-AR



Ordering Matrix		
Model	Finish	Accessories
[]	[]	
EN-1260-P-AR	BK WT	<i>See table below</i>

Ordering Example (model – finish) : EN-1260-P-AR-BK

Product Details	
Description:	Low Voltage plug-in Class II electronic transformer designed to be used as portable or plug-and-play style transformer. Contains an on/off toggle switch at the base and a 6' detachable cord.
Catalog Number:	EN = Advanced electronic circuitry 1260 = 12 volt , 60 watt P = Portable Plug-In AR = Auto-Reset
Input:	120V (50/60Hz)
Output:	12V
Min Load:	20W
Max Load:	60W
Max Input Amp:	0.53A (@ 120V)
Transformer Frequency:	20 khz. True RMS meter is required to read the high frequency output.
Listing:	U.L. listed, File Number E204239.
Accessories:	MTB-01 – Multiple Terminal Block

Specification Features
<ul style="list-style-type: none"> U.L. 2108 listed Class II electronic low voltage transformer. Built-in auto reset, soft start, short and overload circuit protection features. The soft start delayed start feature extends lamp life by delaying the abrupt inrush current to the lamp. Class II transformers are inherently protected and power limited, protecting the lighting system from both normal and abnormal short circuits 5 year W.A.C. Lighting product warranty.