
HR-8411

4" Low Voltage Downlight Trim



PRODUCT DESCRIPTION

Recessed adjustable trim with interior step baffle. For use with HR-8400 series low voltage housings.

FEATURES

• Step baffle, 35° adjustment from vertical recessed downlight

Baffle/Trim

- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory

Black/Brushed Nickel

• Handles surfaces up to 3/4" thick

Finish

ΒN

• 5 year WAC Lighting product warranty

ORDER NUMBER

Model #

WAC LIGHTING Responsible Lighting®

Fixture Type:	
Catalog Number	:
Project:	
Location:	

SPECIFICATIONS

Construction: Durable stamped metal construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED or Halogen 12V MR16 lamps (order separately). 50W or 75W maximum, see individual housing for wattage rating.

Finish: Abrasion resistant powder coat painted or plated metal finish. Available in Black baffle with Brushed Nickel trim (BN), Copper Bronze baffle with Copper Bronze trim(CB), Black baffle with White trim (WT), or White baffle with White trim (WT/WT).

Standards: UL & CUL Listed, Suitable for damp locations

HR-8411	CB	Copper Bronze/Copper Bronze							
HK-0411	WT	Black/White	ACCESSORIES						
	WT/WT	White/White			AMB	Amber	LENS-16-UVF	UV Filter	
Model #	Fir	nish			BLU	Blue	LENS-16-FR	Frosted Lens	
		LENS-16- Co	Color Lens	GRN	Green	LENS-16-SPR	Spread Lens		
HR-84	11 -				RED	Red	LENS-16-BEL	Beam Elongating Lens	
Evenender I					YEL	Yellow	LENS-16-HCL	Honeycomb Louver	
Example: F	HR-8411-CB								

^{ı∣3}∕16"

4" Low Voltage Ho	usings (Required)		Model	Volta	ige	Transformer	Output	Installation	Rating
	4 ⁴ / ₄ " 		HR-8402E		120V	Electronic	12V, 50W max	New Construction	Non-IC
A.	6%" + 4¼" + - min 14½" - max 24½"		HR-8402HL*		120V	Magnetic	12V, 75W max	New Construction	Non-IC
and the second	7%6" <u>i</u> min 14½" min 14½" max 24½"		HR-8403	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	IC Airtight
	5½" 		HR-8402	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	Non-IC
	4% <u>6</u> " 13%6	 	HR-8401E		120V	Electronic	12V, 50W max	Remodel	Non-IC
	<u> </u>	5%" 5%"	HR-8401	H HF	120V 277V	Magnetic	12V, 50W max	Remodel	Non-IC

*Not Compatible with HR-D418 or HR-D418-S Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to %" for remodel & %" for new construction.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2014