

HR-LED371

3" LEDme® Shower Trim

WAC LIGHTING

Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Square recessed shower trim with interior woven lens. For use with HR-LED309 series housings.

FEATURES

- Less than 1/8" thick, super low profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2%"
- · Narrow flood beam spread
- 100,000 hour rated life
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to ¾" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction. Two heavy gauge E-clips hold trim firmly to housing.


Light Source: Utilizes three 3W LED's (included with housing). See individual housing for wattage rating.


Finish: Powder coat paint or plated metal finish. Available in Chrome (CH) and White (WT).

Standards: UL Listed for wet locations.

ORDER NUMBER

Model #	Finish	Trim			
HR-LED371	CH	Chrome			
	WT	White			





Beam Angle: 32°

HR-LED371 –

Example: HR-LED371-WT

COMPATIBLE HOUSINGS (ORDER SEPARATELY)

Rating	Model #	Installation	Color Temp		Watt	Lumens	CRI	Input	Current	Dimensions			Cutout
IC-Rated	HR-LED309-NIC	New Contruction	27 30	2700K 3000K	5.8W	295 295	85 85	120V 50/60Hz	450mA	L: 15-24½"	W: 6¾"	H: 51/8"	3%"
	HR-LED309-RIC	Remodel	35 40	3500K 4000K		314 375	80 75			L: 11¼"	W: 3¾"	H: 51/8"	3%"
Non-IC	HR-LED309-N	New Contruction	27 30	2700K 3000K	8W	413 413	85 85	120V 50/60Hz	700mA	L: 15-24½"	W: 6¾"	H: 51/8"	3%"
	HR-LED309-R	Remodel	35 40	3500K 4000K		440 515	80 75			L: 11¼"	W: 3¾"	H: 51/8"	3%"

Example: **HR-LED309-NIC-27** See individual housing spec sheets for complete information.

WAC Lighting

www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585