


<b>CATALOG NUMBER</b>	<b>TYPE</b>
<b>PROJECT</b>	

**120V TRACK SINGLE CIRCUIT**

**"H" Series Track**



H system Adapter



**Catalog Information**

Model	Description	Length	Width	Height	Finishes
HT2	2 foot single circuit track section	23 3/4"	1 3/8"	3/4"	BK, BN, DB, WT
HT4	4 foot single circuit track section	47 1/4"	1 3/8"	3/4"	BK, BN, DB, WT
HT6	6 foot single circuit track section	71"	1 3/8"	3/4"	BK, BN, DB, WT
HT8	8 foot single circuit track section	94 1/2"	1 3/8"	3/4"	BK, BN, DB, WT

Ordering Example (model– finish): HT6-DB

**Product Details**

<b>Description:</b>	120V Single Circuit, 3-Wire style track system. Supplied with two end caps and mounting hardware.	
<b>Materials:</b>	Aluminum extrusion with copper bus wire.	
<b>Capacity:</b>	20 Amps rated, 120V.  It is common practice to use tracks at 80% capacity to insure compatibility with dimmers and connectors (1920W maximum).	
<b>Mount:</b>	Can be installed on drywall, or suspended ceilings.	
<b>Finish:</b>	<b>BK – Black</b> <b>WT – White</b>	<b>DB – Dark Bronze</b> <b>BN – Brushed Nickel</b>
<b>Listing:</b>	UL & CUL Listed. 5 year WAC Lighting product warranty.	

**Specification Features**

- Track is field cuttable and easily installed on dry wall, plaster, wood, or suspended ceilings. Both track and connectors are polarized.
- Electrical connections available to supply power from the end of track, at the junction of two tracks, or anywhere along the track or run
- Use compatible track luminaires and QUICK CONNECT™ adapters with each system ( example H track with H system track heads or EN-HQ50AR adapters)
- Track may be suspended from flat, sloped ceilings. Use SK suspension kits (specify SK18, SK24, SK36, SK48, available in Black or White). For sloped ceilings, order SK14 adapter. Suspension rods may be field cut without retaping by using SK05 adapters, sold in pairs.