


HR-LED85

LEDme® Button Light



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Designed for recessed or surface mounted installations, delivering strong light output with the latest in LED technology.

FEATURES

- 1 1/2" aperture
- Recessed or surface mounting
- Quick and easy installation
- Includes 72" lead wire
- Replaceable LED module
- 3000K color temperature
- 50,000 hour rated life
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Watt	Lumens	Efficacy
3W*	180	60.0 Lm/W*

*Power consumption may vary depending on the efficiency of the system being used.

SPECIFICATIONS

Construction: Die-cast aluminum fixture, stamped steel housing for surface mount. Glass beam spread lens.

Wiring: Includes 72" pre-installed wires that lead out through the top for connection to a remote driver.

Driver: Remote LEDme® magnetic low voltage driver required (see below). Dimming and non-dimming drivers available. Use a multiple terminal block to wire up to 6 fixtures in a neat under cabinet installation without the use of open splices (see below).

Light Source: Includes three 1W, 3000K LEDs. CRI: 80. Replacement module available.

Dimming: May be dimmed using a LEDme® dimmable driver and a magnetic low voltage (MLV) dimmer in a home-run wiring set up only.

Mounting: *Recessed*– 2 1/8" cutout hole. Compression springs hold fixture firmly in place. *Surface*– Screw housing cover to surface, compress springs and insert into cover. **Not recommended for use in ceiling.**

Finish: Black (BK), Dark Bronze (DB) and White (WT) powder coat, electroplated Brushed Nickel (BN), Copper Bronze (CB) and Chrome (CH).

Standards: UL & CUL Listed.


ORDER NUMBER

Model #	Finish
HR-LED85	BK Black
	BN Brushed Nickel
	CB Copper Bronze
	CH Chrome
	DB Dark Bronze
	WT White

HR-LED85 –

Example: **HR-LED85-DB**

FINISHES



REPLACEMENT MODULE

Model #	Watt	Color Temp
RM3X1-30-HR	3 x 1W	3000K

RETROFIT RECESSED HOUSING

Model #	Finish
HR-LED-COV	BK, BN, CB, CH, DB, WT

Use to replace low voltage HR-88 and HR-86 button lights using existing wiring and cutout.

LEDme® REMOTE BUTTON LIGHT DRIVERS

Model #	Dimming	Wattage	Dimensions
LED-350MA03-RB	No	3W	L: 6 1/2" W: 1 5/8" H: 1 1/4"
LED-350MA09-RB	No	9W	L: 7 1/8" W: 3 1/8" H: 1 5/8"
LED-350MA12-RB	No	12W	L: 7 1/8" W: 3 1/8" H: 1 5/8"
LED-350MA09-DIM-RB	Yes	9W	L: 6 5/8" W: 2" H: 1 1/8"
LED-350MA12-DIM-RB	Yes	12W	L: 6 5/8" W: 2" H: 1 1/8"

See next pages for complete driver spec sheets.

MULTIPLE TERMINAL BLOCK

Model #	Dimensions
MTB-01	L: 3 1/4" W: 1 1/4" H: 7/8"

12.5A max accommodates up to 6 output connections for 14 AWG wires.

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
615 South Street • Garden City, NY 11530
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
168 Brea Canyon Road • City of Industry, CA 91789
Phone (800) 526.2588 • Fax (800) 526.2585


HR-LED85

LEDme® Button Light Drivers

Non-Dimming Drivers

FEATURES

- Magnetic low voltage driver
- Works in *BOTH* series and home-run wiring set ups
- Power up to 4 HR-LED85 fixtures
- Plug and play terminal blocks (for 9W and 12W models)
- Constant current for optimized performance
- Surge protection
- Short circuit protection
- UL and CUL Listed
- 5 year WAC Lighting product warranty



ORDER NUMBER and SPECIFICATIONS

	LED-350MA03-RB	LED-350MA09-RB	LED-350MA12-RB
Input Voltage	120VAC, 50/60Hz	120VAC, 50/60Hz	120VAC, 50/60Hz
Input Current	0.1A max	0.15A max	0.2A max
Output Voltage	12VDC	12VDC	12VDC
Output Current	350mA	350mA	350mA
Wattage	3W max	9W max	12W max
Powers up to	1 Button Light	3 Button Lights	4 Button Lights

Dimming Drivers

FEATURES

- Magnetic low voltage driver
- May be dimmed with magnetic low voltage (MLV) dimmer
- Works *ONLY* in home-run wiring set up
- Power up to 4 HR-LED85 fixtures
- Plug and play terminal blocks
- Constant current for optimized performance
- Surge protection
- Short circuit protection
- UL and CUL Listed
- 5 year WAC Lighting product warranty



ORDER NUMBER and SPECIFICATIONS

	LED-350MA09-DIM-RB	LED-350MA12-DIM-RB
Input Voltage	120VAC, 50/60Hz	120VAC, 50/60Hz
Input Current	0.15A max	0.2A max
Output Voltage	12VDC	12VDC
Output Current	350mA	350mA
Wattage	9W max	12W max
Powers up to	3 Button Lights	4 Button Lights

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
615 South Street • Garden City, NY 11530
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
168 Brea Canyon Road • City of Industry, CA 91789
Phone (800) 526.2588 • Fax (800) 526.2585