InvisiLED[®] Outdoor Palette

LED Tape Light Power Supplies & Controllers



WACI	LIGH	TING
Respor	nsible Li	ghting®

Fixture Type:	
Catalog Number:	
Project:	

Location:



POWER SUPPLY	Model #	Input	Output	Dimensions	Description
Remote Class 2 DC Transformer	EN-O24100-RB2-T	120V-277V AC	24V DC/96W	117⁄16″×4½″×1 ¹⁵ ⁄16″	6' lead wire included. Requires a minimum load of 1W. Max run 100W: 40'

CONTROLLERS		Model #	Dimensions	Description
Wireless Palette Controller		LED-TO24-WS	4"×2½"×5%"	 Wireless connection to Master Controller. Use to switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Includes 2 AAA batteries.
Master Controller	7	LED-TO24-CM	4"×2"×1½"	Powers one run up to 40'. Connects and controls all slave controllers for runs over 40'.
Slave Controller	7	LED-TO24-CS	4"× 2"× 1½"	Connects to Master Controller for runs over 40'. Uses a separate 120V power supply. Powers up to another 40', a new Slave Controller is needed for every 40' extension.

CONTROLLER COM	IPONENTS	Model #	Dimensions	Description
Joiner Cable	7-	LED-TO24-IC6 LED-TO24-IC12 LED-TO24-IC72 LED-TO24-IC72	6" 12" 72" 120"	Extends distance between Power Supply and Master Controller.
Signal wire	Q	LED-TO24-SW60 LED-TO24-SW120	60″ 120″	Connects Master Controller and Slave Controller.
DMX Signal Wire	\mathcal{O}	LED-TO24-MW60 LED-TO24-MW120	60″ 120″	Connects DMX system to Master Controller.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2014