InvisiLED® Pro Outdoor

WAC LIGHTING

Accessories

Responsible Lighting®



Model #	Dimensions	Description
LED-TO24-IC6 LED-TO24-IC12 LED-TO24-IC72 LED-TO24-IC120	6" 12" 72" 120"	Connects two sections of InvisiLED® Classic Outdoor.
LED-TO24-X	wires: 5" each connectors: ¾" each	"X" connector has one male and three female connectors and can be used to easily customize your design layout.
LED-TO24-Y	wires: 5" each connectors: ¾" each	"Y" connector has one male and two female connectors and can be used to easily customize your design layout.
LED-TO24-EC	5%" × 5%" × 3%"	Use to terminate every run to protect against contaminants. Seal cut end with silicone after adding end cap.
LED-TO24-C1	1½"×¾"×¼"	For installation on non-flat surfaces where there is no edge contact. 2 clips per ft are recommended for straight runs.
LED-TO24-C2	7/8" × 3/8" × 1/4"	For installation on non-flat surfaces, allows for contact on one edge. 2 clips per ft are recommended for straight runs.
LED-TO24-C3	5%" × 5%" × 1/4"	For installation on non-flat surfaces, allows for contact on both edges. 2 clips per ft are recommended for straight runs.
LED-TO24-CH1 LED-TO24-CH5	12" × 5%" × ½" 60" × 5%" × ½"	Rigid, non-flexible channel for mounting to a straight, solid surface.
֡֡֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜	LED-T024-IC6 LED-T024-IC12 LED-T024-IC72 LED-T024-IC120 LED-T024-X LED-T024-Y LED-T024-C1 LED-T024-C1 LED-T024-C1	LED-TO24-IC12