
R-421

4" Line Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®





PRODUCT DESCRIPTION

Recessed trim with open reflector. For use with R-400 series Line voltage downlight housings.

FEATURES

- Durable stamped metal construction
- · Retention clips hold trim firmly to housing
- · Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Location:

Construction: Durable stamped metal construction. Three heavy gauge retention clips firmly hold trim to housing.


Lamp: Utilizes LED PAR20 lamp or medium base incandescent. Incandescent lamps are rated for up to 50W watts max. Compact Fluorescent lamps are rated for 13 watts max. Lamps are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish. Reflector is Clear. Trim is available in Brushed Nickel (BN) or White (WT).

Standards: UL & CUL Listed. Suitable for damp locations.

ORDER NUMBER

Model	Finish	Reflector/Trim
R-421	BN CL/WT	Clear/Brushed Nickel Clear/White



Example: R-421-CL/WT

FINISHES

BN





LED PAR20 LAMP (ORDER SEPARATELY)

PAR20LED-10N30 BK Black WT White

4" Line Voltage Housings (Required)		Model	Installation	Rating	Voltage
IC-Rated New Construction	43/16" min 12" max 25"	R-4025-N-ICA	New Construction	IC – Airtight Ready	
Non-IC New Construction	43/16" 	R-4005-N-A	New Construction	Non-IC – Airtight Ready	120V
Non-IC Remodel	4½" ————————————————————————————————————	R-401S-R-A	Remodel	Non-IC – Airtight Ready	

Non-IC housings require $3^{\prime\prime}$ of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585