R-633

6" Line Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

PRODUCT DESCRIPTION

Recessed trim gimbal ring - 20° adjustment from vertical. For use with R-600 series Line voltage downlight housings.

FEATURES

- · Secured to lamp holder bracket by steel springs
- · Provided with foam rubber gasket around outer perimeter
- · Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable stamped metal construction. Secured within lamp housing by steel spring clips. Provided with foam rubber gasket around outer perimeter.

Lamp: Utilizes LED PAR30 lamp or medium base incandescent lamps. Incandescent lamps are rated for up to 75W watts max. Lamps are ordered separately.


Finish: Abrasion resistant powder coat painted or plated metal finish. Trim is available in Brushed Nickel (BN) or White (WT).

Standards: UL & CUL Listed. Suitable for damp locations.

ORDER NUMBER

Model Finish

R-633 BN Brushed Nickel WT White



Example: R-633-BN

FINISHES

BN





LED PAR30 LAMP (ORDER SEPARATELY)

PAR30LED-L14N30 BK Black WT White

Housings (Required)		Model	Installation	Rating	Voltage
IC-Rated New Construction	7½" 6½" min 12" max 25"	R-602D-N-ICA	New Construction	IC – Airtight Ready	120V
IC-Rated Remodel	73 <u>4</u> " 123 <u>4</u> "	R-603D-R-ICA	Remodel	Te /iiiiig/iciteday	1207

Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to $\frac{3}{4}$ " for remodel & $\frac{3}{4}$ " for new construction.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585