


CATALOG NUMBER	TYPE
PROJECT	

5" LINE VOLTAGE DOWNLIGHTS

R-520








Ordering Matrix				
Series	Model	Finish(Baffle/Trim)		
R	520	BK/WT	BN	BZ WT/WT

Ordering Example (series – model number – finish): R-520-BK/WT

Product Details	Specification Features
<p>Description: Recessed trim with interior step baffle. For use with R-5XX series Line voltage downlights.</p> <p>Materials: Durable stamped metal construction. Secured within lamp housing by steel spring clips. Provided with foam rubber gasket around outer perimeter.</p> <p>Lamping Utilizes medium base incandescent or 4-pin CFL lamps. Incandescent lamps are rated for up to 75W watts max. Compact Fluorescent lamps are rated for 26 watts max. Lamps are ordered separately.</p> <p>Finish: Abrasion resistant powder coat painted or plated metal finish. Baffle is available in Black (BK), Bronze(BZ) , Brushed Nickel(BN) or White (WT) . Trim is available in Brushed Nickel (BN), Bronze(BZ) or White.</p> <p>Listing: UL & CUL Listed. Suitable for damp locations.</p>	<ul style="list-style-type: none"> • Handles surfaces up to 1" • 5 year W.A.C. Lighting product warranty.

Compatible Housings(Sold separately)

<p>R-500-N-UA</p> <p>IC/NON-IC Rated. Air tight. New Construction</p> <ul style="list-style-type: none"> • IC rated: 50W PAR30, 50W R30 , 40W A19 • NON-IC rated: 75W PAR30, 75W R30 , 60W A19 		<p>R-501-R-UA</p> <p>IC/NON-IC Rated. Air tight. Remodel housing.</p> <ul style="list-style-type: none"> • IC rated: 50W PAR30, 50W R30 , 40W A19 • NON-IC rated: 75W PAR30, 75W R30 , 60W A19 	
<p>R-F502-N-ICA</p> <p>IC Rated. Air tight. New Construction 13W Max. CFL</p>		<p>R-F503-R-ICA</p> <p>IC Rated. Air tight. Remodel housing 13W Max. CFL</p>	
<p>R-F504-N-A</p> <p>NON-IC Rated. Air tight. New Construction 26W Max. CFL</p>		<p>R-F505-R-A</p> <p>NON-IC Rated. Air tight. Remodel housing 26W Max. CFL</p>	