


CATALOG NUMBER	TYPE
PROJECT	

5" LINE VOLTAGE DOWNLIGHTS

R-540



Ordering Matrix

Series	Model	Finish(Baffle/Trim)
[]	[]	[]
R	540	WT/WT

Ordering Example (series – model number – finish): R-540-WT/WT

Product Details

Description: Recessed trim with scoop wall wash and step baffle. For use with R-5XX series Line voltage downlights.

Materials: Durable stamped metal construction. Secured within lamp housing by steel spring clips. Provided with foam rubber gasket around outer perimeter.

Lamping Utilizes medium base incandescent or 4-pin CFL lamps. Incandescent lamps are rated for up to 75W watts max. Compact Fluorescent lamps are rated for 26 watts max. Lamps are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish. Trim and baffle are available in White.

Listing: UL & CUL Listed. Suitable for damp locations.

Specification Features

- Handles surfaces up to 1"
- 5 year W.A.C. Lighting product warranty.

Compatible Housings(Sold separately)

R-500-N-UA

Air tight.
New Construction
NON-IC rated:
75W PAR30, 75W R30 ,
40W A19



R-501-R-UA

Air tight.
Remodel housing.
NON-IC rated:
75W PAR30, 75W R30 ,
40W A19



R-F502-N-ICA

IC Rated. Air tight.
New Construction
13W Max. CFL



R-F503-R-ICA

IC Rated. Air tight.
Remodel housing
13W Max. CFL



R-F504-N-A

NON-IC Rated. Air tight.
New Construction
26W Max. CFL



R-F505-R-A

NON-IC Rated. Air tight.
Remodel housing
26W Max. CFL

