


615 South Street Garden City, NY 11530 Tel:516-515-5000 Fax:516-515-5050 www.waclighting.com

CATALOG NUMBER	<u>TYPE</u>
PROJECT	

6"LINE VOLTAGE DOWNLIGHTS

R-622





Ordering Matrix					
Series	Model	F	inish(B	affle/Trin	n)
R	622	BK/WT	BN	BZ	WT/WT

Ordering Example (series - model number - finish): R-622-BK/WT

	Prod	uct	Deta	IIS
--	------	-----	------	-----

Description: Recessed trim with interior step baffle. For use with R-6XX

series Line voltage downlights.

Materials: Durable stamped metal construction. Secured within lamp

housing by steel spring clips. Provided with foam rubber gasket

around outer perimeter.

Lamping Utilizes medium base incandescent or 4-pin CFL lamps.

Incandescent lamps are rated for up to 60W watts max.

Compact Fluorescent lamps are rated for 32 watts max. Lamps

are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish.

Baffle is available in Black (BK), Bronze (BZ), Brushed

Nickel(BN) or White (WT) . Trim is available in Brushed Nickel

(BN), Bronze (BZ) or White.

Listing: UL & CUL Listed. Suitable for damp locations.

Specification Features

- Handles surfaces up to1"
- 5 year W.A.C. Lighting product warranty.

Compatible Housings(Solo	d separately)		
R-600D-N-A NON-IC Rated. Air tight. New Construction A19 60W		R-601D-R-A NON-IC Rated. Air tight. Remodel housing. A19 60W	
R-602D-N-ICA IC Rated. Air tight. New Construction A19 40W		R-603D-R-ICA IC Rated. Air tight. Remodel housing. A19 40W	
R-660S-N-A NON-IC Rated. Air tight. New Construction Shallow housing. A19 60W		R-661S-R-A NON-IC Rated. Air tight. Remodel shallow housing. A19 60W	
R-F605D-N-ICA IC Rated. Air tight. New Construction 13W Max. CFL		R-F605D-N-ICA IC Rated. Air tight. Remodel housing. 13W Max. CFL	
R-F607D-N-A NON-IC Rated. Air tight. New Construction 32W Max. CFL		R-F608D-R-A NON-IC Rated. Air tight. Remodel housing 32W Max. CFL	