Model: WL-LED310

LEDme[®] Step Light



PRODUCT DESCRIPTION

Circular window LEDme® Step Light. Designed for safety and style on stairways, patios, decks, balcony areas, walkways and building perimeters. Features an architectural design. Energy efficient for long-lasting indoor and outdoor lighting solutions. Creates an attractive, romantic impression at night. Colored lights can be used for way finding.


FEATURES

- · Direct wiring, no driver needed
- Low profile, flush to wall aesthetics with no visible hardware
- 40,000 hour rated life
- Balanced lighting, free of shadows with minimum glare
- Up to 200 fixtures can be connected in parallel
- Replaceable LED module
- 5 year WAC Lighting product warranty

ORDER NUMBER


Model		Light	Color	Finish		Lumens
WL-LED310	120V	с	White	BN*	Brushed Nickel	115
				BZ	Bronze	115
				WT	White	115
		АМ	Amber	BN*	Brushed Nickel	71
				BZ	Bronze	71
				WT	White	71
		RD	Red	BN*	Brushed Nickel	7
				BZ	Bronze	7
				WT	White	7
		BL	Blue	BN*	Brushed Nickel	13
				BZ	Bronze	13
				WT	White	13


*Brushed Nickel Finish is for interior use only



Example: WL-LED310-C-WT

SPACING RECOMMENDATIONS FOR OPTIMAL LIGHT DISTRIBUTION





waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC LIGHTING


Responsible Lighting®

Fixture Type:

Catalog Number:

Project:

Location:



SPECIFICATIONS

Construction: Die-cast aluminum

Power: Direct wiring, no remote driver needed Input voltage: 120VAC 50/60Hz

Light Source: 3000K Samsung HV-AC High Power LED, CRI: 85 Total power consumption of 3.9W


Mounting: Supplied with junction box for recessed installation Suitable for new construction or retrofit installations. See next page for spacing recommendations

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer Approved dimmers: Lutron Nova-T NTELV-300 & NTELV-600, Lutron Vietri VTELV-600, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600

Standards: IP66, UL & cUL listed for wet locations

FINISHES





Mount in center of stair as close to the upper tread as possible. For best results use one light per step for steps narrower than 5'.

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2016