
RIALTO LED - model: 886LED

LED Low Voltage Track Luminaire







Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Energy efficient track head using a pre-installed MR16 LED lamp. Fixture is specifically designed to ensure proper lamp fit. For use with WAC Lighting's 120V Track system and compatible with other manufacturer's track (consult factory for specific brands).

FEATURES

- · 360° horizontal rotation and 90° vertical aiming
- Two screws for locking aiming angle
- · 34° beam spread
- · Fully enclosed back to prevent light leaks

- Easily re-lamped from the front
- · Adapters in dark bronze and brushed nickel finish to match track finishes
- 25,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum alloy housing and spun metal shade. Clear %" tempered glass lens included.

Transformer: Soft start electronic transformer designed to prolong lamp life, with auto reset and short circuit protection. Input voltage: 120VAC/60Hz. 1W minimum load.

Lamp: 12V MR16 LED (included).

Dimming: Dims to 1% with electronic low voltage (ELV) dimmer.

Finish: Electroplated Antique Bronze (AB) and Antique Nickel (AN). Includes black LED lamp.

Standards: UL & CUL Listed.

FIXTURE PERFORMANCE


Color Temp	Watt	Lumens	Efficacy	CBCP	CRI
3000K	6.4	360	56.3 Lm/W	850	81

LAMP PERFORMANCE



0° Aiming Angle (ceiling to floor)

Distance	FC	L	W
6 ft	24	3.7	3.7
8 ft	13	4.9	4.9
10 ft	9	6.1	6.1
12 ft	6	7.3	7.3



FC	L	W
8	8.1	5.2
5	10.8	6.9
3	13.5	8.6
2	16.2	10.4

ORDER NUMBER

Systen	า	Model #	Fini	sh
LHT HHT JHT	L Track H Track J Track	886LED		Antique Bronze Antique Nickel



Example: LHT-886LED-AN

FINISHES







WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 S Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585