


TUBE ARCHITECTURAL - model: DS-CD **WAC LIGHTING**

LED Ceiling Mounts Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Step inside the world's finest museums, public spaces, corporate offices and luxury homes to see that each of their architectural accents and design elements is showcased with superior grade lighting. The integration of cutting edge designs and advanced technologies is achieved when award-winning WAC luminaires are specified for the next project.

FEATURES

- IP65 rated, ETL & cETL wet location listed
- Meets 2013 California Title 24 Efficiency
- Energy Star® rated
- Solid aluminum construction
- ANSI compliant warm/neutral LED bins, for the finest color consistency possible
- Universal driver (120V-220V-277V)
- 0-10V Dimming

SPECIFICATIONS

- **Rated Life:** 80,000 hours
- **CRI:** Up to 90

ORDERING NUMBER

Model	Diameter	Watt	Beam	Color Temp	Finish
DS-CD	05 5"	24W	S Spot	927 2700K (90CRI)	BK Black
				27 2700K	
	06 6"	42W	N Narrow	930 3000K (90CRI)	WT White
				30 3000K	
	08 8"	54W	F Flood	30 3000K	BZ Bronze
				35 3500K	
					GH Graphite

DS-CD - -

Example: **DS-CD05-S27-BZ**

Size	Watts	Beam	Color Temp	CRI	Lumens	CBCP	Efficacy
5"	24W	Spot	2700K	90	1071	4870	47 Lm/W
			2700K	85	1260	5730	53 Lm/W
			3000K	90	1210	5438	53 Lm/W
			3000K	85	1360	6110	57 Lm/W
5"	24W	Narrow	2700K	90	1067	3094	46 Lm/W
			2700K	85	1255	3640	52 Lm/W
			3000K	90	1242	3119	54 Lm/W
			3000K	85	1395	3505	58 Lm/W
5"	24W	Flood	2700K	90	986	2057	43 Lm/W
			2700K	85	1160	2420	48 Lm/W
			3000K	90	1228	2390	53 Lm/W
			3000K	85	1380	2685	58 Lm/W
6"	42W	Spot	2700K	90	1579	8662	38 Lm/W
			2700K	85	1815	10190	43 Lm/W
			3000K	90	1709	10204	41 Lm/W
			3000K	85	2035	11465	48 Lm/W
6"	42W	Narrow	2700K	90	1566	4012	37 Lm/W
			2700K	85	1800	4720	43 Lm/W
			3000K	90	1688	4659	40 Lm/W
			3000K	85	2010	5235	48 Lm/W
6"	42W	Flood	2700K	90	1557	2512	37 Lm/W
			2700K	85	1790	2955	43 Lm/W
			3000K	90	1693	2982	40 Lm/W
			3000K	85	2015	3350	48 Lm/W
8"	54W	Spot	2700K	90	2860	20455	53 Lm/W
			2700K	85	3365	24065	62 Lm/W
			3000K	90	3230	21796	60 Lm/W
			3000K	85	3670	24490	68 Lm/W
8"	54W	Narrow	2700K	90	4015	28660	74 Lm/W
			2700K	85	4890	34515	71 Lm/W
			2700K	90	2890	6851	54 Lm/W
			2700K	85	3400	8060	63 Lm/W
8"	54W	Flood	3000K	90	3318	7907	61 Lm/W
			3000K	85	3770	8885	70 Lm/W
			3500K	85	4005	9390	74 Lm/W
			2700K	90	2886	4633	53 Lm/W
8"	54W	Flood	2700K	85	3395	5450	63 Lm/W
			3000K	90	3322	5407	62 Lm/W
			3000K	85	3775	6075	70 Lm/W
			3500K	85	4005	6490	74 Lm/W

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center


168 Brea Canyon Road • City of Industry, CA 91789

Phone (800) 526.2588 • Fax (800) 526.2585

TUBE ARCHITECTURAL - model: DS-PD

LED Ceiling Mounts

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Step inside the world's finest museums, public spaces, corporate offices and luxury homes to see that each of their architectural accents and design elements is showcased with superior grade lighting. The integration of cutting edge designs and advanced technologies is achieved when award-winning WAC luminaires are specified for the next project.

FEATURES

- IP65 rated, ETL & cETL wet location listed
- Meets 2013 California Title 24 Efficiency
- Energy Star® rated
- Solid aluminum construction
- ANSI compliant warm/neutral LED bins, for the finest color consistency possible
- Universal driver (120V-220V-277V)
- 0-10V Dimming

SPECIFICATIONS

- **Rated Life:** 80,000 hours
- **CRI:** Up to 90

ORDERING NUMBER

Model	Diameter	Watt	Beam	Color Temp	Finish
DS-PD	05 5"	24W	S Spot	927 2700K (90CRI)	BK Black
				27 2700K	
	06 6"	42W	N Narrow	930 3000K (90CRI)	WT White
				30 3000K	
	08 8"	54W	F Flood	35 3500K	BZ Bronze
				GH Graphite	

DS-PD - -

Example: **DS-PD05-S27-BZ**

Size	Watts	Beam	Color Temp	CRI	Lumens	CBCP	Efficacy
5"	24W	Spot	2700K	90	1071	4870	47 Lm/W
			2700K	85	1260	5730	53 Lm/W
			3000K	90	1210	5438	53 Lm/W
			3000K	85	1360	6110	57 Lm/W
5"	24W	Narrow	2700K	90	1067	3094	46 Lm/W
			2700K	85	1255	3640	52 Lm/W
			3000K	90	1242	3119	54 Lm/W
			3000K	85	1395	3505	58 Lm/W
5"	24W	Flood	2700K	90	986	2057	43 Lm/W
			2700K	85	1160	2420	48 Lm/W
			3000K	90	1228	2390	53 Lm/W
			3000K	85	1380	2685	58 Lm/W
6"	42W	Spot	2700K	90	1579	8662	38 Lm/W
			2700K	85	1815	10190	43 Lm/W
			3000K	90	1709	10204	41 Lm/W
			3000K	85	2035	11465	48 Lm/W
6"	42W	Narrow	2700K	90	1566	4012	37 Lm/W
			2700K	85	1800	4720	43 Lm/W
			3000K	90	1688	4659	40 Lm/W
			3000K	85	2010	5235	48 Lm/W
6"	42W	Flood	2700K	90	1557	2512	37 Lm/W
			2700K	85	1790	2955	43 Lm/W
			3000K	90	1693	2982	40 Lm/W
			3000K	85	2015	3350	48 Lm/W
8"	54W	Spot	2700K	90	2860	20455	53 Lm/W
			2700K	85	3365	24065	62 Lm/W
			3000K	90	3230	21796	60 Lm/W
			3000K	85	3670	24490	68 Lm/W
8"	54W	Narrow	2700K	90	4015	28660	74 Lm/W
			2700K	85	4015	28660	74 Lm/W
			2700K	90	2890	6851	54 Lm/W
			2700K	85	3400	8060	63 Lm/W
8"	54W	Flood	3000K	90	3318	7907	61 Lm/W
			3000K	85	3770	8885	70 Lm/W
			3000K	85	4005	9390	74 Lm/W
			2700K	90	2886	4633	53 Lm/W
8"	54W	Flood	2700K	85	3395	5450	63 Lm/W
			3000K	90	3322	5407	62 Lm/W
			3000K	85	3775	6075	70 Lm/W
			3500K	85	4005	6490	74 Lm/W

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

168 Brea Canyon Road • City of Industry, CA 91789

Phone (800) 526.2588 • Fax (800) 526.2585