

Sensi[™] Touch Wi-Fi Thermostat

Designed with you in mind. Easy install for you, upgraded features and convenient comfort for your homeowners. It's contractor-tested and homeowner-approved.



HD COLOR TOUCH SCREEN

The high-definition color display features easy-to-read temperatures and intuitive menus.



GEOFENCING

Geofencing automatically changes temperatures based on the location of the homeowner's smartphone.



SMART ALERTS


Smart alerts notify homeowners of extreme temperature or humidity levels.



SMART HOME COMPATIBLE

Compatible with smart home platforms Apple HomeKit, Amazon Alexa and Wink.









EASY TO INSTALL

Installation made simple with built-in level, illuminated backplate and easy-click terminals.



EASY TO CONNECT TO WI-FI

Easy step-by-step guide in the app to connect to Wi-Fi.



CONTRACTOR-ON-CALL

The Sensi app stores your contact information so when your customer needs service, you're just a tap away.



ENERGY SAVING FEATURES

With features like geofencing, flexible scheduling and remote access, homeowners can save money without compromising their comfort.



MULTI THERMOSTAT CONTROL

Easy management for schools and light commercial applications.



CIRCULATING FAN

Improves air quality when a custom run time is set.



DID YOU KNOW?









Sensi Touch Wi-Fi Thermostat 1F95U-42WF

Making installation even easier

- Built-in level for picture-perfect mounting
- Terminal lights for increased visibility while wiring
- Large, easy-to-read terminal labels on the back plate
- Easy-click terminals, eliminating the need for a screwdriver
- Size that covers the existing footprint of most thermostats



SPECIFICATIONS

ELECTRICAL RATING

20 to 30 VAC, 50/60 Hz 1.5 Amps maximum per terminal 2.5 Amps maximum (all terminals combined)

STANDARD SYSTEMS

Single-stage gas, oil, electric Single-stage heat pump Multi-stage gas, oil, electric Multi-stage heat pump

SETPOINT RANGE

50°F to 99°F (10°C to 36°C)

ACCESSORIES

Wallplate: F61-2689 (6.75" x 4.50") Thermostat guard: F29-0198

DIMENSIONS

5.63" W x 3.38" H x 1.00" D

Heat (conventional gas/oil/elect): Cool (central air): Heat pump (heat and cool): Heat pump (aux):

COMPATIBILITY

Conventional heating and cooling systems:

Heat pump*, heat only and cool only systems:

SENSI ALERT

High temperature: Low temperature: High humidity: Loss of heat/cool:

RATED DIFFERENTIALS (@ 6°F / HR) Fast

Med Slow 0.5°F 0.75°F 1.9°F 0.9°F 1.2°F 1.7°F 0.9°F 1.2°F 1.7°F 0.5°F 0.75°F 1.9°F

Power Source

Hardwired only (c-wire)

Hardwired only (c-wire)

Trigger

Above 99°F Below 45°F Above 78% Temp goes up or down 5°F during cycle

STORAGE

-20° to 150°F (-29° to 65°C) 0%-90% RH non-condensing

OPERATING AMBIENT

32°F to +105°F $(0^{\circ}C \text{ to } +41^{\circ}C)$

OPERATING HUMIDITY

90% non-condensing max

DISPLAY TEMPERATURE RANGE

32°F to +99°F (0°C to 37°C)

*The Sensi thermostat provides automatic dual fuel control without an outdoor sensor. A fossil fuel kit may be added if user selectable balance point settings are desired.

| Model | Program Options | | | Max Stages Heat/Cool | | Applications | | | | Power Source | | Selectable Performance Features | | | | | | Comfort & Convenience Features | | | | | |
|-----------------|---------------------------------------|-------|----------------------|-------------------------|-----------|------------------|-------------|-----------|-----------------|-----------------|-----------------|---------------------------------|-----------------|-----------------------------|--------------------|------------------|-------------------|--------------------------------|---------------------------|-----------------|----------------|-----------------------------|------------------|
| Model Number | Wi-Fi Control/Smart Home Qualified | 7 Day | Non- Programmable | Conventional | Heat Pump | Gas/Oil/Electric | 3 Wire Zone | Millivolt | PTAC Compatible | Battery | Hardwired (24V) | Auto Changover | Circulating Fan | EMR/ Early Start Program | Temperature Limits | Humidity Display | Dual Fuel Control | Remote Sensor | Filter Change Reminder | Auto DST Adjust | Keypad Lockout | Cont. backglow w/ Common | Permanent Memory |
| 1F95U-42WF | • | • | • | 2/2 | 4/2 | • | • | | • | | • | • | • | • | | • | • | | | • | • | • | • |





‡Thermostat has internal jumper on RC and RH. On two transformer systems, clip red jumper wire on thermostat.



R-4569-6