

WINCO®

Quality Generators Since 1927

35PTOC-3



Generator End:

- 100% copper windings - longer life and improved motor starting
- Single phase, 4 pole
- Rotating field brush type
- Maintenance free bearings
- Class H Insulation
- Buck boost transformer regulated

Features:

- 4-wire Anderson full power plug included
- Large 3" voltmeter
- Low harmonic content appropriate for sensitive loads
- Cast iron gear case with 540 RPM 1 3/8" splined input shaft
- Compact for easy storage
- Square D circuit breakers
- Protective PTO shield
- Rodent protection
- Helical gears for smooth operation
- Ground lug
- Lifting eye

Accessories (optional):

- PTO drive shaft (tumbling bar)
- Off road PTO trailer kit
- Manual transfer switches
- 1000 RPM gearcase



POWER RATING (watts)	35,000
AMPS (1)	146
VOLTS	120/240
PHASE	Single
VOLTAGE REGULATION	+/- 5%
RATING	125°C
TYPE	4 POLE REVOLVING FIELD
GENERATOR SPEED	1800 RPM
VOLTAGE CONTROL	BUCK BOOST TRANSFORMER
PTO INPUT SPEED	540 (2)
REQUIRED INPUT HP (3)	70
MOTOR STARTING (Code G)	20 HP
120 VOLT RECEPTACLES	1x NEMA 5-20R
120/240 VOLT RECEPTACLES	1x NEMA 6-50R
DIMENSIONS (LxWxH)	39" x 20" x 21"
NET WEIGHT	524 lbs
SHIP WEIGHT	534 lbs
WARRANTY	3 YR

NOTES: (1) Unity (1.0) power factor (2) 1000 RPM factory installed gear case optional. (3) Recommended HP at PTO of tractor for full rated output. Each 2 HP provided at the PTO will result in 1kW electrical output up to the nameplate reading.

Presented by:

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057