

ASSEMBLY AND INSTALLATION INSTRUCTIONS FOR

ITEM #137-25/# 140-25#137-28/# 140-28#137-34/# 140-34

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

Installation steps:

1. Turn off the electricity at the Fuse or Circuit Breaker before installation.
2. Attach the Cross Bar to the Outlet Box by using 2PCS of Mounting Screws upwards.
3. Thread the Bottom Central Tube to the Central Connector and then thread the Top Central Tube to the Bottom Central Tube, then attached the whole cluster to the Connector, adjust the cluster to be vertical and Fix with the Small Screw.
4. Choose a certain length of the Chain you need, and weave the Fixture Wire and the Ground Wire through the Chain links, then attached one of the Adjustable Loops to the Top Loop and the other one to the Loop.
5. Thread the fixture wire and the Ground Wire through the Top Nut, Top Loop, Adjustable Loop, Canopy, Nipple-1 and the Cross Bar in order.
6. Make wire connections with Wire Connectors:
 - Connect the Wire (W/ marking) from the light to the Black Wire from the Outlet Box.
 - Connect the Wire (W/O marking) from the light to the White Wire from the Outlet Box.
 - Attached the Ground Wire and House Ground Wire to the Cross Bar with a Green Screw.Carefully tuck wires back into the Outlet Box.
7. Attached the Canopy to the Cross Bar by inserting the Nipple-1, then secure with the Top Loop and Top Nut.
8. Put the Glass into the Metal Ring and carefully raise up the Glass and Metal Ring to the fixture and attached the end of the Small Chain to the Bottom Hanging Hook.
9. Install bulbs (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Candle Cover.)
10. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.

