WALL

DESIGNER: ROBERT BRUNNER A streamlined fusion of black, or white glass and stainless steel with a light, floating effect are sandwiched together in a reimagining of the classic range hood.



MODEL White Glass w/ Stainless Steel	ALA-M90BWX ALA-M90BBX	ALA-E42BWX ALA-E42BBX						
Black Glass w/ Stainless Steel	ALA-MYUDDA	ALA-E42DDA						
Size	90cm (35-3/8")	42"						
Internal Blower CFM*	290, CBI-290A	290, CBI-290A 600, CBI-600A						
Internal Blower CFM*	600, CBI-600A							
In-line Blower CFM*	1,000, PBN-1000A	1,000, PBN-1000A						
External Blower CFM*	1,000, CBE-1000	1,000, CBE-1000						
Max. Sones	3.2–6	3.2–6						
Controls	Capacitive Touch	Capacitive Touch						
Speed Levels	3	3						
Auto Delay-Off	Yes	Yes						
CleanAir Function**	Yes	Yes						
Tri-Level Lighting Yes	LED Strip x 2 (6W)	LED Strip x 2 (6W)						
	Yes Decorative Mesh x2	Yes						
		Decorative Mesh x2						
	Yes, RF	Yes, RF						
Recirculating	Yes	Yes						
Duct Cover Extension	Yes	Yes						
DUCT SPECIFICATIONS								
Vertical Internal Blower	6"	6"						
Vertical In-Line/External Blower	10" to 8"***	10" to 8"***						
Horizontal	NA	NA 120V - 60Hz						
AC INPUT	120V - 60Hz							
AC POWER****	Max. 0.3 Amps	Max. 0.3 Amps						
OPTIONAL ACCESSORIES								
Recirculating Kit	ZRC-01LA	ZRC-01LA						
Duct Cover Extension Kit	Z1C-00LA (up to 12' ceiling)	Z1C-00LA (up to 12' ceiling)						
Make-Up Air Kit	MUA006A (600 CFM)	MUA006A (600 CFM)						
•	MUA008A (1,000 CFM)	MUA008A (1,000 CFM)						
MOUNTING HEIGHT RANGE [†]	24" - 36"	24" - 36"						

HOOD HEIGHT CALCULATOR

CEILING HEIGHT		8′	8.5'	9′	9.5′	10′	10.5′	11'	12'
STANDARD DUCT COVER	Ducted Mounting Height [†]	24" - 32"	24" - 36"	24" - 36"	28" - 36"	34" - 36"	NA	NA	NA
	Recirc. Mounting Height	24" - 29"	24" - 35"	24" - 36"	28" - 36"	34" - 36"	NA	NA	NA
EXTENSION DUCT COVER	Ducted Mounting Height [†]	NA	NA	NA	24" - 32.5"	24" - 36"	24" - 36"	24" - 36"	24" - 36"
	Recirc. Mounting Height [†]	NA	NA	NA	24" - 29.5"	24" - 35.5"	24" - 36"	24" - 36"	24" - 36"

^{*}Blower sold separately.

WARRANTY

1 Year parts, 1 year labor 1 Year parts, 1 year labor



^{***}CleanAir turns your hood on once every four hours for 10 minutes on speed one.

***10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with external and in-line blowers.

*****AC power listed above is for hood with lights only. For blower specifications please refer to the blower spec sheet.

**Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.

AYFRS

WALL

DESIGNER: ROBERT BRUNNER











Wireless Remote Control



Front



Side

