


# OPTICA WALL

The daringly asymmetrical architecture of Optica's tempered glass and steel structure is yet another example of the Elica Collection's assertively future-forward design aesthetic. It is balanced, harmonious, and yet fresh and unexpected. The kind of brilliance that will transform any kitchen into a showplace.



# ELICA COLLECTION





†Ductless (Recirculating); louver holes exposed. Note: if necessary order the proper duct cover extension kit.

### OPTICA

4	$\sim$	
vi.		 - 1

## SIZE

# **NET WIDTH**

\*PERFORMANCE Internal Blower CFM \*\*In-Line Blower CFM Sones (Internal Blower)

### COLOR/FINISH

Stainless Steel w/Glass

#### FEATURES & **ACCESSORIES**

Controls Speed Levels **Boost Speed** Lighting **Dual Level Lighting** RF Remote Passive Silencer

#### DUCT **SPECIFICATIONS**

\*\*Ducting Recirculating **Duct Cover Extension Option** (up to 12' ceiling)

#### EOP-E36ASX

# 36" 35 7/8"

600 1100

Soft Touch 3

Nο Halogen 20w 12v x 2

Νo Νo Yes

Yes Yes

#### EOP-E42ASX

42" 41 7/8"

> 600 1100

S

Soft Touch 3

Νo Halogen 20w 12v x 2

Νo Νo Yes

8" Yes Yes

#### Mounting Heights (Ducted) (Louver holes hidden)

Mounting Heights (Recirculating) (Louver holes exposed) Min. ceiling height 7'4". Hood mounted 24" above cooking surface; 60" from floor.

Min. ceiling height 7'8". Hood mounted 24" above cooking surface; 60" from floor. Max. ceiling height 9'10". Hood mounted 32" above cooking surface; 68" from floor.

Max. ceiling height 9'10". Hood mounted 32" above cooking surface; 68" from floor.

<sup>\*</sup> Blowers not included with hoods, order blower option separately. \*\* Run 10" round duct work from in-line blower to the ceiling bracket. Before duct work passes through the ceiling bracket, use a 10" to 8" transition adaptor (included) and run 8" duct.





