

Product Name:	ABT-26S-TS
Description:	<p>TempLog Premier Solid Door Laboratory Refrigerator 26 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Adjustable operating temperature range: 1°C - 10°C Touch Screen Digital Temperature Display and Alarm Module Password-protected control panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active temperature scale bar display Resettable 1-point min/max history Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Electronic troubleshooting guide Electronic QR Code to access Owner's Manual & technical support contact information Adjustable alarm volume Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm Operation indicator Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Four adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Casters with footed brake Probe access port (3/8") White powder-coated steel exterior and interior CFC-free refrigerant (R134a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 20 3/8"W x 36 ½"D x 79 ¾"H Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP UL/C-UL listed Shipping weight: 343 lbs.</p>