| | Product Name: | ABT-CS-23 |
|--|---------------|--|
| | | |
| vacuum insulated), right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature: 1°C to 10°C Four adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Casters with footed brake LED interior lights are safety shielded and switch controlled One GFCI protected duplex electrical outlet | Description: | 23 Cu. Ft. Capacity One swing glass door, self-closing (energy efficient, double pane, vacuum insulated), right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature: 1°C to 10°C Four adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Casters with footed brake LED interior lights are safety shielded and switch controlled One GFCI protected duplex electrical outlet One 2" access port with spring loaded self-closing, gasketed metal cover Probe access port (3/8") Powder coated steel white interior and exterior High density urethane foam cabinet insulation CFC-free refrigerant (R134a), foam insulation and packaging One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 26 7/8"W x 34 ¾"D x 79 ¾"H Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP UL/C-UL listed |