

Product Name:	ABT-HCPP-49-TS
Description:	<p>TempLog Premier Pharma Laboratory Refrigerator  49 Cu. Ft. Capacity  Two swing stainless steel doors  Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds  Touch Screen Temperature Display &amp; Alarm Module:  Microprocessor temperature controller  Adjustable operating temperature range: 1°C - 10°C  Touch Screen Digital Temperature Display and Alarm Module  Password-protected control panel  Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit  Active temperature scale bar display  Resettable 1-point min/max history  Digital 24-hour temperature chart  Temperature &amp; alarm event data logging  USB port for data transfer and software updates  Real-time operational display clock  4-20mA output  Electronic troubleshooting guide  Electronic QR Code to access Owner's Manual &amp; technical support contact Information  Adjustable alarm volume  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Door ajar alarm  Low battery alarm  Operation indicator  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Remote alarm contacts  Six shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handles  Swivel casters (adds 5" to height)  Interior light  Probe access port (3/8")  Stainless steel interior/exterior  High density urethane foam cabinet insulation  HFC-free refrigerant (R290a), foam insulation and packaging  Quality certified with 100% unit temperature testing  Three year parts and labor warranty, plus an additional two year compressor parts warranty  Exterior dimensions: 54 1/8 "W x 31 5/8 "D x 83 5/16" H with casters;  78 5/16 "H without casters  Cycle defrost  115V, 60 Hz, 5.8 Amps, 1/3 HP  UL/C-UL listed  Shipping weight: 470 lbs.</p>