

Product Name:	ABT-LS-72
Description:	<p>Standard Glass Door Laboratory Refrigerator</p> <p>72 Cu. Ft. Capacity</p> <p>Three swing glass doors, self-closing (energy efficient, double pane vacuum insulated)</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Remote alarm contacts</p> <p>Adjustable operating temperature: 1°C to 10°C</p> <p>Twelve adjustable shelves (adjustable in ½" increments)</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handles</p> <p>Swivel casters (3 ½")</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Probe access port (3/8")</p> <p>Powder coated steel white interior and exterior</p> <p>High density urethane foam cabinet insulation</p> <p>CFC-free refrigerant (R134a), foam insulation and packaging</p> <p>One year parts and labor warranty, plus an additional four year compressor parts warranty</p> <p>Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 10 Amps, 3/4 HP</p> <p>UL/C-UL listed</p> <p>Shipping weight: 743 lbs.</p>