

FS30L7MED



24.63" x 18.5" x 17.75" (H x W x D)

Compact commercially listed manual defrost all-freezer with alarm, hospital grade cord, external thermometer and lock

Highlights:

Commercially listed to NSF-7 standards

Compact size is ideal for countertop use

Designed for general purpose use in medical and scientific facilities

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Compact dimensions	Sized for easy use on top of counters
Fully finished cabinet	Allows the unit to be used freestanding
Manual defrost	Static cooling system for improved temperature stability
Temperature alarm	High/low temperature alarm audibly warns when interior is out of set range
Temperature readout	Alarm includes current and high/low temperature
Adjustable thermostat	Dial thermostat located inside the unit
Factory installed lock	Keyed lock for a secure interior
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup

FS30L7MED Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Shipping Weight	53.0 lbs. (24 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101059587
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

