## accucold

# **ARG31PVBIADA**



#### 32" x 18.5" x 22.63" (H x W x D)

Performance series Pharma-Vac 2.83 cu.ft. ADA height glass door commercial all-refrigerator for the display and refrigeration of vaccines; designed for freestanding or recessed installation

#### **Highlights:**

32" height fits under lower ADA compliant counters

Recessed installation capable for use in 19" wide spaces

Intelligent microprocessor digital temperature controller

#### **Product Features:**

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines	
ADA Compliant	32" height is designed to fit under ADA compliant counters	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use	
Commercial design	Meets UL-471 commercial standards	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2°C to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com



## accucold

### **ARG31PVBIADA Specifications:**

Overview	
Height of Cabinet	32.0" (81 cm)
Width	18.5" (47 cm)
Width with Door Open	19.0" (48 cm)
Depth	22.63" (57 cm)
Depth with Handle	24.38" (62 cm)
Depth with door at 90°	40.0" (102 cm)
Capacity	2.83 cu.ft. (80 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.75
Voltage/Frequency	115 V AC/60 Hz
Weight	102.0 lbs. (46 kg)
Shipping Weight	113.0 lbs. (51 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.41oz.
High Side PSI	280.0
Low Side PSI	90.0
Interior Light	Yes
Interior Light Temperature Range	Yes 2°C to 8ºC
-	
Temperature Range	
Temperature Range Dimensions	2°C to 8°C
Temperature Range Dimensions Interior Height	2°C to 8°C 24.0" (61 cm)
Temperature Range Dimensions Interior Height Interior Width	2°C to 8°C 24.0" (61 cm) 15.25" (39 cm)

Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	5.5" (14 cm)



