SBC58BLBIADACFTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap cold brew coffee dispenser with stainless steel wrapped door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Dual tap commercial grade tap kit includes everything you need to serve flat cold brew coffee on draft

Commercially listed to NSF-7 standards

Product Features:

| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters | |
|------------------------------|--|--|
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings | |
| Built-in capable | Front-breathing design allows fully recessed installation under counters | |
| Complete dual tap kit | Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs | |
| Stainless steel wrapped door | 304 grade stainless steel for a professional look with lasting durability | |
| Professional handle | Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally | |
| Adjustable thermostat | Interior dial thermostat ensures easy temperature management | |
| Automatic defrost | No-frost operation for minimum user maintenance | |
| Reversible door | User-reversible door swing allows you to easily adjust to better accommodate your setting | |

 \checkmark





SBC58BLBIADACFTWIN Specifications:

| Overview | | |
|-------------------------------|--------------------|--|
| Height of Cabinet | 32.0" (81 cm) | |
| Height to Hinge Cap | 32.25" (82 cm) | |
| Width | 23.63" (60 cm) | |
| Depth | 22.75" (58 cm) | |
| Depth with Handle | 24.25" (62 cm) | |
| Depth with door at 90° | 45.0" (114 cm) | |
| Capacity | 5.5 cu.ft. (156 L) | |
| Defrost Type | Automatic | |
| Door | Stainless Steel | |
| Cabinet | Black | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Sanitation | ETL-S | |
| Amps | 1.2 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 110.0 lbs. (50 kg) | |
| Shipping Weight | 120.0 lbs. (54 kg) | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| UPC | 761101069623 | |
| Kegerator | | |
| Door Swing | RHD | |
| Reversible | Yes | |
| Tap Kit | Yes | |
| Height with Tap | 47.5" (121 cm) | |
| Number of Taps | 2 | |
| Thermostat Type | Dial | |
| Interior Light | Yes | |
| Fan Type | Exterior | |
| Refrigerant | R600a | |
| Refrigerant Amount | 0.64 oz. | |
| High Side PSI | 180.0 | |
| Low Side PSI | 80.0 | |
| Inter Height | 25.75" (65 cm) | |
| Interior Width | 21.0" (53 cm) | |
| Interior Depth | 17.75" (45 cm) | |
| Compressor Step Height | 6.5" (17 cm) | |
| | | |

| Compressor Step Width | 21.0" (53 cm) |
|-----------------------|---------------|
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | 34º to 43ºF |
| | |



