

American Standard

Method Three Installation Instructions for Undermount Series "The Big Sinks"

Notes for Fabricator/Installer

1. Installation is based on the use of a cabinet with a 24" front-to-back dimension.
2. Installation of Undermount Series - The Big Sinks is based on "sandwiching" the rim of the sink between the countertop and 1/2" plywood sheet. The 1/2" plywood sheet rests on top of the cabinet. The front edge of the countertop must be built-up to hide this 1/2" underlayment.
3. Method Three is based on installing Undermount Series sinks, including the plywood reinforcement sheet, with the countertop at the fabricator's shop.
4. American Standard accepts no liability for damage to the solid surface countertop, or sink fixture, during installation.
5. Inspect the sink fixture for any shipping damage, prior to installation. Do not install a damaged unit.
6. Aesthetics are essential to presentation of the installed sink unit. Take the necessary care to ensure that the exposed silicone joint is kept to a minimum, the sink is properly aligned to the cut-out, and excess silicone is cleaned from the sink.
7. We have supplied within the sink carton: sink strainers, 1/8" masonite template, and a product use and care sheet + Product Warranty.
8. Undermount sinks have a striking silk polished profile on the sink rim. To highlight this unique design feature, our installation system reveals up to 1/16" of the sink rim flat.

Call Customer Service

1-800-442-1902
Monday through Friday
8:00 A.M. to 7:30 P.M. EST

Technical Customer Service

1-800-442-1902
Monday through Friday
8:00 A.M. to 6:00 P.M. EST
Saturday
8:00 A.M. to 3:00 P.M. EST

Write Customer Service

Customer Care at American Standard
P.O. Box 6820
1 Centennial Plaza
Piscataway, NJ 08855-6820

The Fabricator/Installer Will Require:

- an assortment of clamps
- a solvent such as methyl hydrate or denatured alcohol
- silicone sealant
- 1/2" plywood sheet

Fabricator Template Preparation

The masonite template supplied has been machined to the exact size and shape of the finished countertop cut-out.

The cut-out will reveal approximately 1/16" of the silk finished sink rim flat.

We recommend that the template be used to create a female template from 1/2" plywood.

Sink Installation Schematic

