


Submitted Model No.:

Specific Features:



▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability. BSP-L-65485LF-LHP Rev. B

BRIZO WIDESPREAD VESSEL LAVATORY FAUCETS

- Charlotte[™] Bath Collection
 Two Handle Widespread Deck Mount
- 3 Hole Sink Applications
- 6" to 16" Centers

STANDARD SPECIFICATIONS:

- Two handle layatory faucet for concealed mounting on 3 hole applications.
- Widespread 6" (152mm) to 16" (406 mm) centers.
- 5" (127 mm) long, 12 3/4" (324 mm) high rigid spout.
- LHP Less Handle Program. See handle options below.
- Control mechanism shall be of the rotating ceramic cylinder type with 90° (1/4 turn) rotation.
- Metal grid strainer with overflow included (RP72412).
- Optional grid strainer without overflow (RP72411), push button pop-up with overflow (RP72414) or push button pop-up without overflow (RP72413).
- Accomodates up to 2 1/2" deck thickness.
- Maximum flow rate 1.5 gpm @ 60 PSI.


WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

- Indicates compliance to ICC/ANSI A117.1
 EPA WaterSense®
 "LF" models verified compliant with .25% weighted average Pb content regulations.



Delta Faucet Company

55 E. 111 th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, Ontario, Canada N5P 4L1 © 2013 Masco Corporation of Indiana