= 2	C o n t e m p o r a r y L i g h t i n g™
-----------------	---

Product Specifications for E20250-03			
Job Name:	Job Type:		
oo rame.	500 Type.		
Quantity:	Comments		
` '			

4	-
	Ī

E20250-03 Graffiti 1-Light Pendant

Finish

Satin Nickel

Lamping Number of Bulb(s) **Light Type** Incandescent **Bulb Type** MB Max Bulb Wattage 100 Max Fixture Wattage 100 **Rated Life** ±2,500 Hours **Rated Lumens** ±1,150 **Color Temp** ±2,700 K Bulb(s) Included No Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

Glass/Shade Red

Other

UPC Code

Material

Measurements Width 6.00" Height 14.50" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height N/A **Max Overall Height** 120.00" Hanging Weight 3.74 lb(s) **Height Adjustable** Yes Slope 120° Chain Length N/A Wire Length 126.00" **Canopy Width** N/A Canopy Height N/A Canopy Length N/A

Product Category

Mini Pendant

	Chinning	
	Shipping	
"	Carton Weight	5.50 lb(s)
"	Carton Width	9.13"
١	Carton Height	9.00"
١	Carton Length	19.88"
١	Carton Cubic Feet	N/A
١	Master Pack	1
١	Master Pack Weight	N/A
١	Master Pack Width	N/A
"	Master Pack Height	N/A
)	Master Pack Length	N/A
3	Master Cubic Feet	N/A
0	UPS Shippable	Yes
١		
"		

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Equivalents

 845094014126
 Incandescent Watts
 N/A

 N/A
 Fluorescent Watts
 N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.