

HALF MOON



MINI



15064 AZT, BBR, WHT

15065 AZT, BBR, BKT, WHT

Ordering Guide & Finish	15064 AZT, BBR, WHT		15065 AZT, BBR, BKT, WHT															
Housing	Cast Aluminum or Cast Brass		Cast Aluminum or Cast Brass															
Lamp Base	12V T3 bi-pin, high temperature porcelain socket		12V T5 wedge base socket															
Supplied Lamp	10-W(VA) Q10T3 (17011) Halogen light source Power usage at 12V AC input VA MAX: 10-W(VA)		6.5-W(VA) 918X (17022) Xenon light source Power usage at 12V AC input VA MAX: 6.5-W(VA)															
Incandescent Lamp Options	N/A		N/A															
LED Lamp Options	2W (18042-18044) see page 137 Compares up to 20W Halogen Light distribution may be affected by location of sockets	2W (18124-18125) see page 138 Compares up to 20W Halogen	2W (18039-18041) see page 137 Compares up to 16W Xenon Light distribution may be affected by location of sockets	2W (18120-18121) see page 138 Compares up to 16W Xenon														
Wiring	72" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		72" of usable #18-2, SPT-1-W leads. Cable connectors supplied.															
Matching Outdoor Path Lights	15360		15005, 15011, 15315, 15326, 15328															
Mounting Access. (Included)	N/A		Post adaptor and Rail adaptor included are stainless steel. Fits standard 4" x 4" post.															
LED Option	See 15764 on page 54		See 15765 on page 54															
Notes	Brass will develop natural patina over time		Brass will develop natural patina over time															
Photometric with Supplied Lamp	Mounting Height	0'	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	Mounting Height	1'	2'	3'	4'	5'	6'	7'
	6'	53	36.1	4.7	.9	.2	-	-	-	-	6'	2.8	.06	.03	-	-	-	-
	12'	13.8	17.3	6.9	2.5	.9	.3	.1	-	-	12'	4.1	.73	.15	-	-	-	-
	30'	2.2	3.2	2.6	2	1.4	.9	.6	.3	.2	30'	1.7	.87	.37	.1	-	-	-