

12V LED/INCANDESCENT PATH & SPREAD

SIMPLICITY  
SIDE MOUNT



15360 AZT

CONTOURS



15333 TZT

Ordering Guide & Finish	15360 AZT		15333 TZT																	
Housing	Aluminum		Aluminum																	
Lamp Base	12V S8 wedge base socket		12V S8 wedge base socket																	
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)		24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																	
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)		18.5-W(VA) 3155K (15599 CLR)																	
LED Lamp Options	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.	2W (18122-18123) see page 137. Compares up to 18.5W Krypton.	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.																	
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		34" of usable #18-2, SPT-1-W leads. Cable connectors supplied.																	
Mounting Access. (Included)	8" In-ground slotted stake		8" In-ground slotted stake																	
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket																	
Notes	N/A		U.S. Patent Pending																	
Photometric with Supplied Lamp	Distance from Light	.5'	1'	2'	3'	4'	5'	6'	7'	8'	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8.9'	9'
	Bottom	20.7	10.8	3.5	1.1	.4	.1	-	-	-	Foot Candles	11.9	6.6	2.58	.88	.28	-	-	-	-