

KOHLER® Roughing-In

K-1109-LA, K-1109-RA PORTRAIT® 5' BATH WHIRLPOOL WITH INTEGRAL APRON

Product Information

Applicable product:	
Bath whirlpool with left drain, integral apron	K-1109-LA
Bath whirlpool with right drain, integral apron	K-1109-RA

Fixture*:	
Bathing well:	
Basin area, bottom	42" (106.7 cm) x 20" (50.8 cm)
Basin area, top	51" (129.5 cm) x 24" (61 cm)
Weight	135 lbs (61.2 kg)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	60 gal (227.1 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A
1-speed	120	60	7

Recommended accessories:	
Clearflo bath cable drain with PVC tubing	K-7213
Clearflo bath cable drain without PVC tubing	K-7214
Clearflo pop-up bath drain	K-7161-AF

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (242 kg/square meter) loading.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

