

KOHLER® Roughing-In

K-1158-H2
BANCROFT™ 5.5'
BATH WHIRLPOOL

Product Information

Applicable product:				
Bath whirlpool	K-1158-H2			
Fixture*:				
Bathing well:				
Basin area, bottom	46" (116.8 cm) x 30" (76.2 cm)			
Basin area, top	57" (144.8 cm) x 34" (86.4 cm)			
Weight	130 lbs 59 kg			
To overflow:				
Water depth	16" (40.6 cm)			
Capacity	95 gal (359.6 L)			
* Approximate measurements for comparison only.				
Included component:				
Cut-out template	1043292-7			
Pump	Heater	V	Hz	A
	1.5 kW	240	50/60	11
Minimum access panel:				
Pump/ control	34" (86.4 cm) W x 15" (38.1 cm) H	required		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control	220-240 V, 20 A, 50/60 Hz
--------------	---------------------------

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (242.3 kg/square meter).

Hot water supply should be 70% of capacity or greater. Installations will vary.

This bath is designed for drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

A minimum access panel is required.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF)

