

KOHLER® Roughing-In

K-1192
SYNCHRONY®
5' BATH WHIRLPOOL

Product Information

Applicable product:	
Bath whirlpool less softgrip grip handles	K-1192
Bath whirlpool less softgrip grip handles, left drain hole, integral flange	K-1192-L
Bath whirlpool less softgrip grip handles, right drain hole, integral flange	K-1192-R

Fixture*:	
Basin area:	
Bathing well	42" (106.7 cm) x 25" (63.5 cm)
Top area	52" (132.1 cm) x 34" (86.4 cm)
Weight	105 lbs (47.6 kg)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	63 gal (238.5 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	58" (147.3 cm) x 40" (101.6 cm)
-----------------	---------------------------------

Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 38 lbs/square foot (183 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

