

Product Information

Applicable products:	
Custom bath whirlpool – drop-in	K-1221-HB
Custom bath whirlpool – drop-in	K-1221-HE

Fixture*:	
Basin area:	
Bathing well	47" (119.4 cm) x 37" (94 cm)
Top area	67" (170.2 cm) x 42" (106.7 cm)
To overflow:	
Water depth	16-7/8" (42.9 cm)
Capacity	122 gal (461.8 L)
Weight	125 lbs (56.7 kg)
* Approximate measurements for comparison only.	

Drop-in cut-out	70-1/4" (178.4 cm) x 46-1/4" (117.5 cm)
-----------------	---

Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater:	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

An access panel required. Provide an access panel that is a minimum of 20" (50.8 cm) W x 15" (38.1 cm) H.

Floor support under whirlpool must provide for a minimum of 49 lbs/square foot (238 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

