

Product Information

Applicable products:	
6' custom bath whirlpool with heater – drop-in	K-1248-HG
6' custom bath whirlpool with heater – drop-in	K-1248-HN

Fixture*:	
Basin area:	
Bathing well	50" (127 cm) x 31" (78.7 cm)
Top area	61" (154.9 cm) x 34" (86.4 cm)
Weight	117 lbs (53.1 kg)
To overflow:	
Water depth	14-1/2" (36.8 cm)
Capacity	86 gal (325.5 L)
* Approximate measurements for comparison only.	

Included components:	
Cut-out template	113927-7

Pump:	V	Hz	A	
1-speed	120	60	7.5	
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

■ Recommended Faucet Area

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (199.9 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

