


Features

- Acrylic
- Oval shape
- Drop-in
- 6 individually adjustable ProFlex_® hydro-massage jets
- Pump with air switch and grounding-type plug-in cord
- Molded lumbar supports and armrests
- Optional K-1491 removable bath pillow
- Optional K-1601 removable footstop
- Optional K-9696 whirlpool trim kit in various finishes
- 60" (1524 mm) x 42" (1067 mm) x 20" (508 mm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.19.7
- UL 1795
- CSA B45.5/IAPMO Z124



SUNWARD_®

BATH WHIRLPOOL

K-1162-S1

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- 0: White
- CP: Polished Chrome
- PB: Vibrant_® Polished Brass
- NA: None applicable
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Description				Colors/Finishes		
K-1162-S1	Bath whirlpool – drop-in (shown)					□ Other		
Recommer	nded Accessories					1		
K-11677	Swiftflo™ adjustable trip lever drain					🗆 PB		
Optional A	ccessories							
Optional A K-576				Oth		NA		
	ccessories Undermount kit					. NA		

Product Specification

The drop-in oval shaped bath whirlpool shall be made of acrylic. Bath whirlpool shall be 60" (1524 mm) in length, 42" (1067 mm) in width, and 20" (508 mm) in height. Bath whirlpool shall have 6 individually adjustable ProFlex hydro-massage jets, a pump with air switch and grounding type plug-in cord. Bath whirlpool shall have molded lumbar supports and armrests. Bath whirlpool shall be Kohler Model K-1162-S1-_____.

SUNWARD_®

Technical Information

Fixture*:						
Bathing well:						
Basin area, bottom	Basin area, 43" (1092 mm) x 21-9/16" (548 mm)					
Basin area, top	asin area, top 53-1/2" (1359 mm) x 32-1/8" (816 mm)					
Weight	0 lbs (50 kg)					
To overflow:						
Water depth 15" (381 mm)						
Capacity	Capacity 57 gal (215.9 L)					
* Approximate measurements for comparison only.						
Pump:		V		Hz		A
1-speed		120		60		7.5
Minimum access panel pump/control:						
20″ (508 mm) W x 15″ (381 mm) H						required
Included components:						
Cut-out template				104	2556-7	
						-

Required Electrical Service


Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):					
Pump/control	120 V, 15 A, 60 Hz				
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.					

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 35 lbs/square foot (171 kg/square meter) loading.

The suction line extends 4-5/8'' (117 mm) beyond the edge of the rim. The pump base extends 1/8'' (3 mm) beyond the edge of the rim. Modify the framing as needed.



Product Diagram

