

Product Information

Applicable products:	
6' custom bath whirlpool with heater – less Softgrip handles	K-1198-HB
6' custom bath whirlpool with heater – Softgrip handles	K-1194-HB
Fixture*:	
Basin area:	
Bathing well	49" (124.5 cm) x 25" (63.5 cm)
Top area	61" (154.9 cm) x 34" (86.4 cm)
Weight	115 lbs (52.2 kg)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	72 gal (272.5 L)
* Approximate measurements for comparison only.	
Drop-in cut-out	70" (177.8 cm) x 40" (101.6 cm)
Pump:	V Hz A
1-speed	120 60 7.5
Heater:	kW V Hz A
	1.5 120 60 12.5
Recommended accessories:	
Adjustable pop-up drain	K-7161-AF

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (173 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

