

### Product Information

Applicable product:	
6' bath whirlpool with Relax Experience	K-1418-CT
Fixture*:	
Basin area:	
Bathing well	48" (121.9 cm) x 27" (68.6 cm)
Top area	60" (152.4 cm) x 30" (76.2 cm)
Weight	140 lbs (63.5 kg)
To overflow:	
Water depth	16" (40.6 cm)
Capacity	94 gal (355.8 L)
* Approximate measurements for comparison only.	
Drop-in cut-out	70-1/2" (179.1 cm) x 40-1/2" (102.9 cm)
Pump:	kW    V    Hz    A
Variable-speed	1.5    240    50/60    11
Recommended accessories:	
Pop-up bath drain	K-7161-AF

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220/240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 45 lbs/square foot (221 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This whirlpool is designed for drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

