

KOHLER® Roughing-In

K-712-G IRON WORKS® 5.5' (1.7 m) BUBBLEMASSAGE™ BATH

Product Information

Applicable product:				
5.5' (1.7 m) BubbleMassage bath			K-712-G	
Fixture*:				
Bathing well:				
Basin area, bottom	47-1/2" (120.7 cm) x 25" (63.5 cm)			
Basin area, top	55" (139.7 cm) x 29" (73.7 cm)			
Weight	500 lbs (227 kg)			
To overflow:				
Water depth	12-5/8" (32.1 cm)			
Capacity	64 gal (242.3 L)			
* Approximate measurements for comparison only.				
Included component:				
Cut-out template		88051-7		
Blower motor:	Heater	V	Hz	A
	300 W	220-240	50/60	3

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Blower motor/control	220-240 V, 15 A, 50/60 Hz
----------------------	---------------------------

Installation Notes

Install this product according to the installation guide.

NOTICE: If the blower motor and check valve are relocated, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under bath must provide for a minimum of 65 lbs/square foot (314 kg/square meter) loading.

Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

