

KOHLER® Roughing-In

K-809-H2, K-809-LH, K809-RH
KATHRYN®
5.5' BATH WHIRLPOOL

Product Information

Applicable products:	
5.5' bath whirlpool – drop-in	K-809-H2
5.5' bath whirlpool for alcove installation – drop-in, left drain	K-809-LH
5.5' bath whirlpool for alcove installation – drop-in, right drain	K-809-RH

Fixture*:	
Bathing well:	
Basin area	45" (114.3 cm) x 25" (63.5 cm)
Top area	58" (147.3 cm) x 29" (73.7 cm)
Weight	510 lbs (231.3 kg)
To overflow:	
Water depth	17-3/4" (45.1 cm)
Capacity (to overflow)	97 gal (365.2 L)
* Approximate measurements for comparison only.	

Pump	kW	V	Hz	A*
	1.5	240	50/60	11
* Approximate measurements for comparison only.				

Cut-out template:	
Drop-in	64-1/2" (163.8 cm) x 34-1/2" (87.6 cm)
Undermount	K-587

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Cast iron bath whirlpools are extremely heavy, making some drop-in installations difficult. For deck-mount installations, splitting the deck/surround is recommended.

The required access panel must be a minimum of 34" (86.4 cm) in width and 15" (38.1 cm) in height.

Floor support under whirlpool must provide for a minimum of 82 lbs/square foot (398 kg/square meter) loading.

The hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7145 or K-7145M)

K-809-H2

