

KOHLER® Roughing-In

**K-5024-T
DARFIELD™
URINAL**

Product Information

Applicable product:	
3/4" top spud urinal	K-5024-T
Urinal complies with ADA requirements when rim is mounted no higher than 17" (43.2 cm) from finished floor. ADA	

Fixture:	
Configuration	3/4" top spud
Spud inlet size	3/4"
Water per flush	0.5 gal (1.89 L) to 1 gal (3.78 L)*
* Designed to use 0.5 gal (1.89 L) to 1 gal (3.78 L) of water when installed with a water saving flush valve.	

Recommended accessories:	
1-1/2" P-Trap	K-9000
0.5 gpf (1.89 lpf) Touchless DC flushometer with WAVE technology	K-10675
0.5 gpf (1.89 lpf) Touchless DC flushometer with TriPoint™ technology	K-10958

Included components:	
3/4" inlet spud	18376
1-1/2" outlet spud	18357
Strainer	85061
1-1/2" tailpiece	38530
Hanger (1 required)	64512
Refer to manufacturer's instructions and local codes for flush valve requirements.	

Installation Notes

Install this product according to the installation guide.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

*Urinal complies with ADA requirement when rim is mounted no higher than 17" (43.2 cm) from finished floor

