

Product Information

| | |
|--|-----------|
| Applicable product: | |
| Bath – airjet trim/White | K-899-G0 |
| Bath – airjet trim/Almond | K-899-G47 |
| Bath – airjet trim/Biscuit | K-899-G96 |
| Bath – airjet trim/Polished Chrome | K-899-GCP |
| Bath – airjet trim/Brushed Nickel | K-899-GBN |
| Bath – airjet trim/Vibrant Polished Nickel | K-899-GSN |
| Bath – airjet trim/Dune | K-899-GNY |

| | |
|---|--------------------------------------|
| Fixture*: | |
| Bathing well: | |
| Basin area, bottom | 49" (1245 mm) x 26-1/2" (673 mm) |
| Basin area, top | 62-1/2" (1588 mm) x 29-1/4" (743 mm) |
| Weight | 435 lbs (197.3 kg) |
| To overflow: | |
| Water depth | 19" (483 mm) |
| Capacity | 90 gal (340.6 L) |
| * Approximate measurements for comparison only. | |

| | |
|-----------------|--------------------------------------|
| Drop-in cut-out | 66-1/2" (1689 mm) x 35-1/2" (902 mm) |
|-----------------|--------------------------------------|

| | | | | |
|---------------|-----|---------|-------|---|
| Blower motor: | kW | V | Hz | A |
| | 300 | 220-240 | 50/60 | 3 |

Required Electrical Service

| | |
|---|---------------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Blower motor/control | 220-240 V, 15 A, 50/60 Hz |

Installation Notes

Install this product according to the installation guide.

NOTICE: If the blower motor and check valve are relocated, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under bath must provide for a minimum of 78 lbs/square foot (386 kg/square meter) loading.

Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7272)

